



READ THIS FIRST



PRIMARY ARMS®

**ULTIMATE WEAPON LIGHT
GEN IV - FLAT DARK EARTH**

MPN: PAWL-2FDEGENIV

UPC: 8 18500 01274 0

Shown in shortened configuration



INTRODUCTION

The Primary Arms Ultimate Weapon Light, Gen IV - Flat Dark Earth is bright, simple, and extremely tough. Gen IV features 900 lumens of white light and a maximum run time of approximately 2.5 hours. Shock proof and water resistant, this tough light is designed specifically for heavy recoiling firearms. Fully captured batteries, high spring force battery contacts, an industry leading LED emitter, aerospace grade materials and premium anodization make the Gen IV the perfect choice for your firearm.

CONFIGURABLE BODY

For applications where a shorter light is desired, turn the head of the flashlight counter-clockwise to unscrew it from the center section. The center section can be turned counter-clockwise to remove it from the mount section. Setting aside the center section, the head of the flashlight can then be attached directly to the mount section by turning clockwise to tighten it. In the shortened configuration, the Ultimate Weapon Light uses two instead of three CR123A batteries. Light output is also reduced by approximately 100 lumens.



REMOVABLE 1913 PICATINNY MOUNT

The 1913 Picatinny rail mount is attached using Philips head screws. Removing the screws allows the mount to be replaced with an ARMS 17 or ADM AD-170 quick disconnect mount. There is no thread locking compound on the

Philips head screws, to make removal easier. If you are not going to replace the mount, we recommend a small drop of blue thread locker on each screw as indicated in the picture above.

TAILCAP PUSH BUTTON

Press the soft rubber button mounted in the tailcap gently to activate the light momentarily. Releasing pressure on the button will immediately deactivate the light. Pressing the button more firmly will result in an audible and tactile “click”, activating the constant-on mode. Once the button has clicked you can remove your hand from the tailcap and the light will stay on. Press firmly again to click the light off.

OPTIONAL TAPE SWITCH

The push button tailcap can be replaced with our matching LFDTST tailcap incorporating a remote tape switch and 8-inch cable. The matte black LBTS tailcap will also fit and function. Press the tape switch to momentarily activate the light, and release again to deactivate the light. The tape switch tailcap is not included and can be purchased separately.



SPECS AND FEATURES

LED: Cree XP-L HD LED

Lifespan: Approx. 50,000 hours

Maximum light output: Approx. 900 lumens

Peak beam intensity: Approx. 21,000 candela

Batteries: Three 3V CR123A (included)

Optional rechargeable: 3.7V batteries (not included)

Maximum run time: Approx. 2.5 hours

Maximum beam distance: Up to 317 yards

Shock proof

Waterproofing: Meets IPX8 standard



PRIMARY ARMS®

Warranty

Your PAWL-2BKGENIV-Flat Dark Earth is covered by the Primary Arms Lifetime Warranty. If a defect due to materials or workmanship, or even normal wear and tear, has caused your product to malfunction, Primary Arms will either repair or replace your product. You can find more details at www.primaryarmsoptics.com.

Email: info@primaryarmsoptics.com

Phone: 713-570-1910

www.primaryarmsoptics.com