



ACSS[®] APOLLO[®] 6.5 CR/.224 V Reticle Manual

ACSS APOLLO 6.5CR/.224V RETICLE

The ACSS Apollo 6.5CR/.224V is a dedicated 6.5 Creedmoor & .224 Valkyrie specific reticle that features easy to use bullet drop compensation and wind holds out to 1,000 yards. Overall, the reticle extends 10 MIL up, left, and right of the center chevron aiming point. Large hash marks are found in 0.2 MIL increments, with smaller marks between them at 0.5 MIL increments.

THE CHEVRON TIP

The ACSS Apollo uses a chevron as the center aiming point of the reticle. Adjust your Windage and Elevation knob positions so that the point of impact coincides with the tip of the chevron. Using the chevron tip allows for an infinitely small point of aim that never covers up the part of the target you want to hit, giving the chevron tip a precision advantage over traditional crosshairs or a center aiming dot.



THE ACSS APOLLO CENTER SECTION

The chevron measures just 0.1 MIL down from center and 0.1 MIL to the left and right of center. Thus, the outer tips of the chevron legs are located 0.1 MIL from center, and 0.2 MIL apart from each other. To the left and right of center, boxes are located at 0.2 MIL intervals with a slightly larger rectangle at 1.0 MIL from center for easy navigation. Small dots (0.05 MIL wide) are spaced at 0.2 MIL intervals above and below center for a total of 1.0 MIL distance.



VERTICAL CENTER SECTION

HORIZONTAL CENTER SECTION



BALLISTICS CHART FOR THE ACSS APOLLO 6.5CR/.224 RETICLE

Instructions for using the ballistics chart: Find your caliber and bullet type. Match up your rifle's muzzle velocity with your altitude above sea level to find the proper zero distance and offset. Plus (+) and minus (-) numbers indicate desired bullet impact in inches above or below the point of aim during initial zeroing. The popular 6.5 Creedmoor bullet types and two .224 Valkyrie bullet types are shown in the chart.

ER stands for Effective Range of Apollo's BDC marks. Beyond the ER distance, bullet flight diverges from the BDC markings by 0.5 MIL or more. While hits are certainly possible on larger targets, precision shooting at small targets beyond the ER range is more difficult. After initial sight-in we recommend fine tuning point of impact at distances of 400-600 yards to maximize precision throughout the BDC.

Example: A 6.5 Creedmoor marksman using 140 grain Hornady ELD bullets at 2,650 fps, at 2,000 feet above sea level, needs to sight in 0.5" high at 100 yards.

6.5 CR 140 Grain Hornady Extremely Low Drag (ELD)					
	Sea Level	+1,000 ft.	+2,000 ft.	+3,000 ft.	
2,750 fps	100 Yard Zero	100 Yard Zero	100 Yard Zero -0.25"	100 Yard Zero -0.5"	
2,700 fps	100 Yard Zero +0.5″	100 Yard Zero +0.25″	100 Yard Zero	100 Yard Zero -0.25"	
2,650 fps	100 Yard Zero +1.0"	100 Yard Zero +0.75″	100 Yard Zero +0.5″	100 Yard Zero +0.25″	
2,600 fps	50 Yard Zero	50 Yard Zero	50 Yard Zero	50 Yard Zero	
6.5 CR 120 Grain Hornady AMAX					
	Sea Level	+1,000 ft.	+2,000 ft.	+3,000 ft.	
2,900 fps 100 Yard Zero -1.0"		100 Yard Zero -1.0"	100 Yard Zero -1.25″	N/A	
2,850 fps	0 fps 800y ER 800y ER 800y ER 900y		100 Yard Zero ER 950y		
2,800 fps	100 Yard Zero ER 800y	100 Yard Zero ER 800y	100 Yard Zero ER 800y	100 Yard Zero ER 800y	
2,750 fps	100 Yard Zero +0.25" ER 600y	100 Yard Zero +0.25" ER 600y	100 Yard Zero +0.25" ER 650y	100 Yard Zero +0.25" ER 700y	

6.5 CR 143 Grain Hornady Precision Hunter ELD-X						
	Sea Level	+1,000 ft.	+2,000 ft.	+3,000 ft.		
2,750 fps	100 Yard Zero	100 Yard Zero -0.25"	100 Yard Zero -0.25"	100 Yard Zero -0.5"		
2,700 fps	100 Yard Zero +0.5"	100 Yard Zero +0.5″	100 Yard Zero +0.25″	100 Yard Zero		
2,650 fps	100 Yard Zero +1.0"	100 Yard Zero +1.0"	100 Yard Zero +0.75″	100 Yard Zero +0.5"		
2,600 fps	50 Yard Zero	50 Yard Zero	50 Yard Zero	50 Yard Zero		
.224 Valkyrie 90 Grain SMK, 88 Grain Hornady ELD Match						
	Sea Level	+1,000 ft.	+2,000 ft.	+3,000 ft.		
2,750 fps	100 Yard Zero +0.25"	100 Yard Zero	100 Yard Zero	100 Yard Zero		
2,700 fps	100 Yard Zero +1.0"	100 Yard Zero +0.5″	100 Yard Zero +0.5″	100 Yard Zero +0.25"		
2,650 fps	50 Yard Zero ER 800y	100 Yard Zero ER 850y	100 Yard Zero ER 900y	50 Yard Zero		
	2,650 fps 50 Yard Zero ER 800y ER 850y ER 900y 50 Yard Zero					

THE ACSS APOLLO OUTER SECTION

At 2 MIL distance left/right from center, the solid crosshair line begins, using alternating upper and lower marks forming a MIL ranging section. These can be used to range targets using extremely fine 0.1 MIL increments. At 3.0 MIL from center, the 0.5 MIL hash marks begin.

TENTH MIL SECTION



BULLET DROP COMPENSATION & WIND HOLDS

Below center, Apollo features a 6.5 Creedmoor & .224 Valkyrie specific bullet drop compensation ladder. Sighting in Apollo so that your rounds impact at the tip of the chevron at 100 yards, hold midway between the 2nd and 3rd dots underneath the chevron for 200 yards. The BDC begins at 300 yards. Hash marks located at increasing 50-yard intervals indicate bullet drop all the way to 1,000 yards, with numbers labeling every 100 yard increase. After determining the correct range to your target, simply aim using the mark that coincides with that range. The hash marks can be subdivided to make even more precise shots on targets at ranges in between those 50 yard increments. For example, if a target is located 475 yards away, aim using a point halfway between the 450 and 500 yard hash marks.

Wind holds are indicated by dots extending to the left and right of the BDC. They are calculated to represent the distance that crosswinds of 5, 10, 15, and 20 mph will push the bullet left or right. For a wind pushing left to right, use the dots on the right side of the BDC. For a wind pushing right to left, use the dots on the left side of the BDC. For example, if the target is located 700 yards away and a 10-mph wind is crossing from left to right, navigate to the "7" line and use the second dots to the right as your point of aim.



RANGING LADDER

Located high and right of center is the ranging ladder. Vertical ranging is calibrated for a 5'10" tall target. Looking through the scope at the target, line up the bottom of the target with the horizontal crosshair. The line that coincides with the top of the target indicates the distance to the target. For example, if the top of the target touches the line with a "4" next to it, the target is 400 yards distant. The ranging lines may be used as reference points to make more precise, yet quick ranging determinations. For example, a 5'10" target with its top midway between the "4" line and the "5" line will be approximately 450 yards away.

Horizontal ranging is calibrated for an 18" wide target. Simply line up the target's width with the appropriate line to determine range to target. For example, an 18" wide target that appears to be the same width as the ranging line with a "6" next to it will be 600 yards away. This method is useful when the target's height is partially obscured, as with a target in tall grass.

RANGING LADDER SECTION



HOW TO USE MILS

7

This reticle features MIL (Milliradian) stadia, which you can use to range targets and communicate with other marksmen or observers. To range using MILs, estimate the height or width of your target. Once you have an estimated target size, find the size of the target in MILs by lining the target up with your MIL subtensions. Depending on your preferred units of measure, you can use different formulas to calculate range estimates: RANGE (METERS) = Target Size (Centimeters) * 10 / Target MILs

RANGE (METERS) = Target Size (Meters) * 1000 / Target MILs

RANGE (METERS) = Target Size (Inches) * 25.4 / Target MILs

RANGE (YARDS) = Target Size (Inches) * 27.78 / Target MILs

VEAPON				DATE	
HOT NO.	DIRECTION/DEFLECTION	ELEVATION	RANGE	АММО	DESCRIPTION
OTES:					

WEAPON					DATE
HOT NO.	DIRECTION/DEFLECTION	ELEVATION	RANGE	АММО	DESCRIPTION
IOTES:					

/EAPON					DATE
HOT NO.	DIRECTION/DEFLECTION	ELEVATION	RANGE	AMMO	DESCRIPTION
OTES:					





LIFETIME WARRANTY

Your Primary Arms SLx 3-18x50 FFP Rifle Scope is covered by the Primary Arms Lifetime Warranty. If a defect due to materials or workmanship, or even normal wear and tear has caused your product to malfunction, Primary Arms will either repair or replace your product. You can find more details about our lifetime warranty at www.primaryarmsoptics.com.

Email: info@primaryarmsoptics.com Toll-free at 855-774-2767 www.primaryarmsoptics.com

For more information on these optics, go to: http://primaryarmsoptics.com/product-category/rifle-scopes/slx/



© Copyright 2023 PRIMARY ARMS, LLC is a registered trademark of PRIMARY ARMS, LLC

For Patent Information go to https://goo.gl/2z62aS