



OMPACT FIRST FOCAL PLANE RD ACSS' GRIFFIN MIL G2

THE ACSS GRIFFIN G2 RETICLE

The ACSS Griffin MIL G2 is an all-new reticle that is purpose-made for optics with a 1-8x magnification range. At 1x magnification, the ACSS Griffin MIL G2 appears as bold crosshairs and a brightly illuminated center aiming point. At 8x magnification, the fine details of the MIL grid come into view. The ACSS Griffin MIL G2 combines an infinitely precise center chevron and both vertical and horizontal ranging stadia for quick range estimation and target engagement.



CLOSE QUARTERS USE

In close quarters, sight acquisition speed is paramount.

At low magnifications, the ACSS Griffin MIL G2 has a simplified aiming reticle with outer crosshairs and boldly illuminated center dot. Your optic's illumination settings will also improve visibility and contrast for consistent acquisition in split-second engagements.

As distance to target increases, the user can increase their magnification, bringing the ACSS Griffin MIL G2's full feature set into view.



PRECISION RANGE SHOOTING

For enhanced precision, increase your scope's magnification and use the chevron tip as your point of aim. The chevron tip provides an infinitely small aiming point without obscuring the part of the target you want to hit for a fast yet very precise sight picture. For further distances, ACSS Griffin MIL G2 includes a detailed MIL grid with built-in bullet drop compensation (BDC) for 5.56 NATO, .308 Win., 6.5 Grendel, and many other cartridges. The BDC starts at the tip of the chevron and ends at the 5th MIL stadia, which acts as an auto-ranging holdover for 600 yards.

SETTING YOUR ZERO

For 5.56 loads, we recommend a 50-yard zero for best results.

For .308 loads, we recommend a 40-yard (near) or 200-yard (far) zero.

To get the best results with any cartridge, use a ballistic calculator to find the optimal zero. The Griffin MIL Reticle can fit a wide variety of cartridges, but you may need to adjust your zero incrementally to ensure your projectile's trajectory aligns with the BDC/MIL stadia.



EXAMPLE ZERO: .308 WINCHESTER



HOW TO ESTIMATE TARGET DISTANCE USING ACSS GRIFFIN MIL G2 RETICLE

Knowing the distance to your target is crucial in using the reticle effectively.

ACSS Griffin MIL G2 offers two methods of range estimation: auto-ranging and MIL ranging. The easiest method is using the reticle's auto-ranging tools, though you can also use the MIL grid itself.

Since this is a first-focal plane reticle, you can perform ranging at any magnification, but using high magnification usually gives the best results.



TARGET AUTO-RANGING

The most efficient way of measuring a target's distance is through the reticle's built-in ranging stadia.

For horizontal stadia ranging, use the width of the chevron and lower MIL stadia to estimate your distance to target. Stadia ranging is calibrated for center mass on a 18"-wide target, such as the torso of a silhouette. At 300 yards, an 18" target will be the exact same width as the chevron. At 400, the target will be the same width as the 2nd MIL stadia. 500-yards and 550-yards targets will match the 3rd and 4th MIL stadia. 600-yard targets will be the same width as the 5th MIL stadia. Beyond this distance, MIL ranging will be necessary.



For vertical stadia ranging, use the height of the numbered stadia on the left and right crosshairs. These stadia are sized to match a 5'10" target at each of their numbered distances, making it easy to estimate a firing solution.

For example, if a 5'10" target matches the vertical stadia marked with an "6", your target is approximately 600 yards away.

HOW TO USE MILS

This reticle features MIL (Milliradian) stadia, which you can use to range targets and communicate with other marksmen or observers.

To range using MILs, estimate the height or width of your target. Once you have an estimated target size, find the size of the target in MILs by lining the target up with your MIL subtensions. Both your MIL grid and vertical ranging stadia have barbells to indicate 5 MIL increments.

Depending on your preferred units of measure, you can use different formulae to calculate range estimates:

- RANGE (YARDS) = Target Size (Inches) * 25.4 / Target MILs
- RANGE (YARDS) = Target Size (Yards) * 1000 / Target MILs
- RANGE (METERS) =

Target Size (Centimeters) * 10 / Target MILs





At low magnification, the outer MIL crosshairs feature subtensions at 5 and 10 MIL increments. The 50 MIL stadia are marked with barbells for quick reference.



WEAPON				DATE		
SHOT NO.	DIRECTION/DEFLECTION	ELEVATION	RANGE	АММО	DESCRIPTION	
NOTES:						

WEAPON				DATE		
SHOT NO.	DIRECTION/DEFLECTION	ELEVATION	RANGE	АММО	DESCRIPTION	
NOTES:						





LIFETIME WARRANTY

Your Primary Arms PLx 1-8x24 compact rifle scope is covered by the Primary Arms Lifetime Warranty. If a defect due to materials or workmanship, or even normal wear and tear has caused your product to malfunction, Primary Arms will either repair or replace your product. You can find more details about our lifetime warranty at www.primaryarmsoptics.com.

Email: info@primaryarmsoptics.com Toll-free at 855-774-2767 www.primaryarmsoptics.com

SCAN HERE for more information on these optics.



©Copyright 2025 PRIMARY ARMS, LLC is a registered trademark of PRIMARY ARMS, LLC

For Patent Information go to https://goo.gl/2z62aS